



YUKSELIS ELEVATOR ROUND MANUFACTURING RANGE			
	yükseliş round small	yükseliş round medium	yükseliş round large
RATED LOAD	600-630kg(Ø1400)	675-800kg(Ø1500)	825-1000kg(Ø1600)
SUSPENSION	2:1	2:1	2:1
MACHINE ROOM	MRL,MR	MRL,MR	MRL,MR
MAX. TRAVEL(m)	60	60	60
MAX. RATED SPEED(m/s)	1.6	1.6	1.6
PIT DEPTH(mm)	v=<1.0m/s 1400 v=1.6m/s 1600	v=<1.0m/s 1400 v=1.6m/s 1600	v=<1.0m/s 1400 v=1.6m/s 1600
CLEAR HEADROOM(mm)	v=<1.0m/s 3800 v=1.6m/s 4000	v=<1.0m/s 3800 v=1.6m/s 4000	v=<1.0m/s 4200 v=1.6m/s 4200
ENTRANCES	Single entrance or through type car	Single entrance or through type car	Single entrance or through type car
DOOR SIZE(mm)	700	800	900
DOOR COVERS	Glass, Hairline Stainless, Decosteel	Glass, Hairline Stainless, Decosteel	Glass, Hairline Stainless, Decosteel
MAX. CABIN DIAMETER(mm)	Ø1400	Ø1500	Ø1600
CABIN COVERS	Glass, Hairline Stainless, Decosteel	Glass, Hairline Stainless, Decosteel	Glass, Hairline Stainless, Decosteel
MIN. SHAFT DIAMETER(mm)	Ø2100	Ø2200	Ø2300
PANORAMIC LIFT	yes	yes	yes
MACHINE	-	-	-
CONTROLLER	-	-	-

ÖLÇEK:	TARİH	02.02.2018	İMZA
ÇİZEN			
ONAY	Selçuk KORKMAZ		
YUKSELIS ROUND ELEVATOR			